



T-Floodlight



Model:	T-Floodlight
Størrelse:	510 x 350 x 87.5 mm
mA/W:	Standard - 120 - 200W
Optik:	Microprismatisk afskærmning - 30° / 60° / 90° beam angle
Ra/Kelvin:	Ra70/80 - 3000K / 4000K / 5000K - Option: RGB
Montering:	Påbyg / Mast / Væg
IP:	66
Maling:	RAL7022 / RAL9005
Tilslutning:	Direkte - kabel
Styring:	On/Off / DALI / 1-10V / Zhaga
IEC62717 (L90B10):	100.000h ved ta 25 grader
Materiale:	Aluminium LM6 - hærdet glas
Vægt kg:	10.5 kg
Sikring B16:	Standard - <48 pr. sikring
Lysstrøm:	Op til 163lm/W

Produktbeskrivelse

T-Floodlight er en effektiv spot til udendørs brug. T-Floodlight er en spot med et enkelt og smalt design, som fås til montering på mast eller påbyg. T-Floodlight egner sig blandt andet til belysning er større udendørsområder eller facader, der ønskes oplyst i mørket.

Transientbeskyttelse L/N-GND: 10kV

Transientbeskyttelse SR driver: 8 kV

LED driver forventet levetid >70.000h.

Armaturets certificering er under CIE EN 60598

1-2 & herunder EN550 15/EMC