



T-Model C



Model:	T-Model C
Størrelse:	Ø170 x 3000 mm / 4000 mm / 5000 mm
mA/W:	Standard - 30W / 40W / 50W
Optik:	Symmetrisk – Option: Asymmetrisk
Ra/Kelvin:	Ra70/80 - 3000K / 4000K
Montering:	Flange
IP:	65
Farve:	RAL7024
Tilslutning:	Direkte - kabel
Styring:	DALI / 1-10V / Dynadim (22:00-06:00, 50%) eller Smartcity
IEC62717 (L90B10):	100.000h ved ta 25 grader
Materiale:	Aluminium - PC afskærmning
Vægt kg:	6 kg. (Armaturhus)
Sikring B16:	Standard - <48 pr. sikring
Lysstrøm:	Op til 114 lm/W

Produktbeskrivelse

T-Model C er et nutidigt belysningsarmatur, der egner sig særdeles godt til moderne arkitektur og bebyggelse. Armaturet er fremstillet med en energieffektiv lyskilde, der sikrer en effektiv og pålidelig belysning i ethvert miljø.

Transientbeskyttelse L/N-GND: 10kV

Transientbeskyttelse SR driver: 8 kV

LED driver forventet levetid >100.000h.

Armaturets certi icering er under CIE EN 60598

1-2 & herunder EN550 15/EMC